

Sensor Requirements Document (SRD)

APPENDICES "A" THROUGH "H," LESS "D"

for

NATIONAL POLAR-ORBITING OPERATIONAL ENVIRONMENTAL  
SATELLITE SYSTEM (NPOESS) SENSORS

Prepared by

Associate Directorate for Acquisition  
NPOESS Integrated Program Office

Revision 1  
29 June 1998

Integrated Program Office  
Silver Spring MD 20910

**APPENDIX A**  
**DEFINITION/GLOSSARY OF TERMS**

## **APPENDIX A DEFINITION/GLOSSARY OF TERMS**

### **10.1 The following definitions apply to this specification and its appendices.**

#### **Airglow**

A natural electromagnetic radiation arising from chemical reactions of upper atmospheric constituents. Airglow occurs as emission continua, atomic lines, and molecular bands, with the brightest contributions arising from atomic oxygen and OH. Airglow extends from the ultraviolet, through visible, to the SWIR spectrum, occurs in the 70-300 km altitude range, and is both temporally and spatially variable.

#### **Albedo (Surface)**

The ratio of the solar electromagnetic power in a specified band reflected from a surface element of the earth to the total in-band power incident upon it.

#### **Ancillary Data**

Any data which is not produced by the NPOESS System, but which NPOESS EDR algorithms require to meet the EDR attributes given in the TRD Appendix D (e.g., terrain height database or conventional surface and upper air observations).

#### **API (Antecedent Precipitation Index)**

An estimate of surface moisture based on rainfall history. API includes both surface water and soil moisture. Soil moisture (columnar %) may be computed from API by dividing API by the depth of the soil (in mm), to yield the equivalent vertical mm of water per unit vertical mm depth of soil. Soil moisture (% by weight) may be computed from API by dividing API by the soil bulk density (requires knowledge of soil type).

#### **Argos**

A satellite-based location and data collection system dedicated to monitoring the environment.

#### **Centrals**

Elements of the NPOESS System which are designated data processing centers. For example, NOAA/NESDIS.

#### **Centrals Element**

The Centrals element will be that equipment and software necessary to ingest and store (temporarily) the RDRs, and process them as necessary into SDRs and EDRs. The currently defined Centrals are AFGWC, NOAA/NESDIS, FNMOC, NAVOCEANO, and 50 WS.

#### **Cloud**

An aggregate of minute non-precipitating water and/or ice particles in the atmosphere above the earth's surface. In this TRD "cloud" is always to be interpreted to mean "detectable cloud," as defined in this glossary.

**Cloud cover**

The fraction of a given area that is overlaid in the local normal direction by clouds. It is the fraction of the earth's horizontal surface that is masked by the vertical projection of clouds.

**Cloud type**

The classification of clouds into the 18 types given in Tables 3-19 and 3-20 of the Federal Meteorological Handbook 1B.

**Common Support Equipment (CSE)**

Support equipment capable of common use by various systems throughout DOD, NOAA, and NASA, as applicable.

**Communications Security (COMSEC)**

Measures taken to provide protection for the transmission of classified and sensitive unclassified information.

**Computer Security (COMPUSEC)**

Measures taken to provide protection for the processing of classified and sensitive unclassified information.

**Critical Failure**

Any fault, failure or malfunction which results in the loss of the System's ability to provide any key attribute of a key EDR or other key parameter (e.g., data access).

**Design Service Life**

The design service life of the satellite is at least 15 years. This includes the time allowed for test, storage, prelaunch checkout, launch and injection, on-orbit, recovery, and contingency time. It includes the 7 year on-orbit design life and up to 3 years of intermittent testing..

**Detectable Cloud**

An aqueous aerosol having a vertical extinction optical depth exceeding 0.03 (*TBR*) in the visible or a contrast with the background exceeding 0.02 (*TBR*) in the visible. Contrast with the background is defined as the difference between the cloud and adjacent background radiance divided by the sum of these two radiances. In this TRD "cloud" is always to be interpreted to mean "detectable cloud."

**Drop Size Distribution**

The number of aerosol, cloud, or rain droplets per specified size interval per unit volume over a specified range of sizes.

**Electron Density Profile**

The density of free electrons as a function of altitude. It is generally derived from both ionospheric sounding data and theory.

**Electronic Counter-Countermeasures (ECCM)**

Measures taken to counter electronic warfare susceptibility and vulnerability of a specific system.

### **Environmental Data**

Environmental data (also termed "mission data") refers to all data: atmospheric, oceanographic, terrestrial, space environmental, and climatic, being sensed and collected by the satellite or derived, at least in part, from these measurements.

### **Environmental Data Records (EDRs)**

Data records that contain the environmental parameters or imagery required to be generated as user products by this TRD as well as any ancillary data required to identify or interpret these parameters or images. EDRs are generally produced by applying an appropriate set of algorithms to Raw Data Records (RDRs)

### **Field Terminals**

DoD tactical field element terminals such as the AN/SMQ-11 and TESS used by the USN; the Mark IV used by the USMC and AF; and the Mark IVB and STT used by the AF and any identified follow-on terminals.

### **Final Operational Capability**

The System final operational capability (FOC) will be met when: a full NPOESS satellite constellation meeting all contractual system requirements is operational; sufficient C3 and mission data recovery resources are available; sufficient crews are trained; sufficient logistics resources are in place to support C3S, data recovery, and IDPS operations; and approval to operate at Falcon AFB is received.

### **Full Mission Capability**

The full mission capability exists when: a full satellite constellation is operational (currently anticipated to be two US and one METOP); sufficient C3 and mission data recovery resources are available; sufficient crews are trained; sufficient logistics resources are in place to support C3, data recovery, and the IDP segment; and approval to operate at Falcon AFB is received.

### **Geoid**

The gravitational equipotential surface corresponding to mean sea level.

### **Geomagnetic Field**

The magnetic field of the Earth.

### **Global Coverage**

Global coverage denotes the observation of all points on the Earth or its atmosphere (with the exception of gaps centered over the poles consistent with the allocated swath width), at least once per given time period, and implies use of recorded data.

### **Global Resolution**

The horizontal spatial resolution (or cell size) required by Centrals to support global coverage EDRs (see the TRD Appendix D).



### **High Data Rate**

Refers to the real time data link to field terminals which contains data at all channels at the smallest scale horizontal spatial resolution (or cell size) required in TRD Appendix D. Note that the smallest scale horizontal spatial resolution (or cell size) is the same resolution as the “regional resolution” required by the Centrals.

### **Horizon**

The actual lower boundary of the observed sky or upper outline of terrestrial objects including nearby natural obstructions.

### **Horizontal Cell Size**

For a parameter which is an estimate of the uniform spatial average of an environmental parameter over a square region of the earth’s surface or within a square layer of the atmosphere, the side length of this square region or layer. (For a parameter which is an estimate of an environmental parameter at a point, the horizontal cell size is defined to be zero.) For a reported parameter not of this type but which is defined for a square region of the earth’s surface or a square layer of the atmosphere (e.g., cloud cover, ice concentration, etc.), the side length of this square region.

### **Horizontal Coverage**

The horizontal spatial extent of the region within which estimates of an environmental parameter are made and reported.

### **Horizontal Reporting Interval**

The spacing between nearest neighbor points in the horizontal direction at which an environmental parameter is estimated and reported. For atmospheric profiles, the horizontal reporting interval applies to the lowest altitude samples.

### **Horizontal Spatial Resolution**

For a scanning imager on a space-based platform, a specified band, and a specified nadir angle, one half of the wavelength corresponding to the earth surface spatial frequency at which the end-to-end system modulation transfer function (MTF) equals 0.5 on the in-track spatial frequency axis or cross-track spatial frequency axis, whichever is greater. The in-track (cross-track) spatial frequency is the earth surface spatial frequency associated with the in-track (cross-track) direction. (See definition of Modulation Transfer Function.)

### **Horizontal Wind Vector Accuracy**

The wind speed error is  $||W_m| - |W_t||$  where:  $W_m$  is the measured velocity and  $W_t$  is the true velocity. The wind direction error is the angular difference between the directions of  $W_m$  and  $W_t$ .

### **Housekeeping**

Functions such as orbit and attitude maintenance, navigation, power, command, telemetry and data handling, structure, rigidity, alignment, heater power, temperature measurements, etc.

**Imagery**

Two-dimensional array of numbers, in digital format, each representing the brightness of a small elemental area.

**Initial Operating Capability**

IOC has been met when: two satellites are operational; sufficient C3 and mission data recovery resources are available to allow all mission data to be processed at all Centrals and 50 percent of field terminals; sufficient crews are trained to allow 24 hours/day, 365 days/year operations at the primary SOC, and to allow backup operations as needed; sufficient sustaining engineering resources are in place to allow for anomaly resolution, for example; sufficient logistics resources are in place to support C3, data recovery, and the IDP segment; and approval to operate at Falcon AFB is received.

**Insolation**

The solar radiation flux at the surface of the earth.

**Ionospheric Scintillation**

The random fluctuation of the amplitude and phase of a radio-frequency signal caused by passing through the ionosphere.

**Key Attribute**

An EDR attribute that is a key parameter of the system. See Key Parameter.

**Key EDR**

An EDR which has a key attribute. See Key Attribute.

**Key Parameter**

A parameter so significant that failure to meet the threshold requirement(s) pertaining to its measurement is cause for the System to be reevaluated or the program to be reassessed or terminated. Key parameters include key attributes of key EDRs and the data access requirement. Key parameter requirements are to be included in the Acquisition Program Baseline. (The term "Key Performance Parameter" is used in the IORD.)

**Key Sensor**

A sensor which is required to meet key parameter requirements.

**Lead**

Any fracture or passageway through sea ice which is navigable by surface vessels.

**Line Replaceable Unit**

The smallest unit that can be removed and replaced without cutting or desoldering connections.

### **Local Average Revisit Time**

The average time interval between consecutive measurements of a parameter at a given location on the earth's surface over a time period much greater than an orbital period. Local average revisit time so defined is a function of location on the earth's surface.

### **Local Refresh**

The maximum time interval between consecutive measurements of a parameter at a given location on the earth's surface over a time period much greater than an orbital period. Local refresh so defined is a function of location on the earth's surface.

### **Local Revisit Time**

The time interval between consecutive measurements of a parameter at a given location on the earth's surface. In general, successive revisit times at the same location will not be equal, and the distributions of revisit times during a given period of time at different locations will be different.

### **Local Time Range**

For an in-situ/in-track measurement, range or ranges of ascending/descending times within which NPOESS spacecraft should be capable of measuring an EDR. Measurements outside of the specified range or ranges are not required.

### **Long Term Stability (TBR)**

The difference between the maximum and minimum short-term means of an estimated parameter over the NPOESS life cycle. This estimate may be the result of a direct measurement, an indirect measurement, or an algorithmic derivation. The short-term mean is defined as the mean of a set of estimates of the parameter satisfying the following three conditions:

- (1) The physical measurements on which the estimates are based, at least in part, are performed within a time period not exceeding TBS days. (This time limit does not apply to databases or other ancillary data sources which may be used to generate the estimate.)
- (2) The set is large enough so that the sample size error (see definition) in the short-term mean is much smaller than the specified long term stability value.
- (3) The true value of the parameter is the same for all estimates in the set.

The third condition is imposed because a long term stability requirement must be met for any true value of the parameter within the measurement range (see definition), not in an average sense over the measurement range. In practice, such as in the analysis of simulation results or measured calibration/validation data, it is understood that measurements will be binned into sets for which the true value of the parameters falls into a narrow range, preferably a range much smaller than the required measurement range. Corrections for known temporal changes in sensor performance characteristics and for differences in sensor performance characteristics from satellite to satellite are considered to be part of the parameter estimation process. Retrospective processing and re-analysis of data is allowed for the purpose of meeting a long-term stability requirement.

The long-term stability  $\rho$  is given by the following formula:

$$\rho = \max\{\mu_N(t)\}_{0 \leq t \leq T'} - \min\{\mu_N(t)\}_{0 \leq t \leq T'}$$

where:  $\mu_N(t)$  is the short-term mean at time  $t$ ,  $T$  is the NPOESS life cycle,  $T'$  is the maximum duration of the period during which measurements contributing to the short-term mean are performed, and the

minimum and maximum are taken over the time period from  $t = 0$ , which is defined to be the beginning of the NPOESS life cycle, to  $t = T - T'$ .

The short-term mean  $\mu_N(t)$  is given by the following formula:

$$\mu_N(t) = (\sum_{i=1,N} x_i(t'))/N, \quad 0 \leq t \leq T - T',$$

where:  $x_i(t')$  is the value obtained in the  $i$ 'th estimate of the parameter at time  $t'$ ,  $\sum_{i=1,N}$  denotes summation from  $i = 1$  to  $i = N$ , and  $t \leq t' \leq t + T'$ . The value of  $N$  is large enough so that the sample size error is much less than the required long term stability value for any time  $t$  in the range  $0 \leq t \leq T - T'$ .

If long term stability is specified as a percentage, the percentage is with respect to the mean  $M_N$  of the short-term mean  $\mu_N(t)$  over the NPOESS life cycle.  $M_N$  is given by the following formula:

$$M_N = (1/(T - T')) \int \mu_N(t) dt$$

where the integral is over the range  $0 \leq t \leq T - T'$ . Long term stability expressed as a percentage is given by:

$$100 \times \rho/M_N$$

where  $\rho$  is defined above.

### **Longwave Radiation**

The radiation that is emitted by the Earth or the atmosphere. It is generally in the spectral wavelength interval between 4 and 50 micrometers.

### **Low Data Rate**

Refers to real time data link to field terminals containing fewer channels and/or coarser resolution than the high data rate real time link.

### **Mapping Uncertainty**

The RMS error (one sigma) in the geolocation of measured or derived data samples, expressed in geodetic coordinates, based on a large number of repetitions of the measurement and/or derivation. An "error" is defined as the difference between the measured or derived value and the true value of a parameter. Mapping uncertainty is due to the combined effect of all systematic and random errors affecting geolocation.

### **Maximum Local Average Revisit Time**

The maximum value of local average revisit time over the set of all locations within a given area of the earth's surface. Unless otherwise specified, the area is defined to be the horizontal coverage region of the measured parameter. Where constraints on the area are specified, e.g., "clear," "cloudy," etc., the area is defined to be the sub-region of the horizontal coverage region satisfying the constraint.

### **Maximum Local Refresh**

The maximum value of local refresh over the set of all locations within a given area of the earth's surface. Unless otherwise specified, the area is defined to be the horizontal coverage region of the measured

parameter. Where constraints on the area are specified, e.g., “clear,” “cloudy,” etc., the area is defined to be the sub-region of the horizontal coverage region satisfying the constraint.

### **Mean Down Time (MDT)**

Mean down time (MDT) is calculated as:

$$\text{MDT} = \frac{\text{total time down from downing events}}{\text{number of downing events}}$$

### **Mean Time Between Critical Failure (MTBCF)**

The total amount of mission time divided by the total number of critical failures during a stated series of missions. Mean time between critical failure (MTBCF) is calculated as:

$$\text{MTBCF} = \frac{\text{operating time}}{\text{number of critical failures}}$$

### **Mean Time Between Downing Events (MTBDE)**

Mean time between downing events is calculated as:

$$\text{MTBDE} = \frac{\text{operating time}}{\text{number of downing events}}$$

### **Mean Time Between Failures (MTBF)**

The mean number of life units during which all parts of the item perform within their specified limits, during a particular measurement interval under stated conditions.

### **Mean Time To Repair (MTTR)**

The sum of corrective maintenance times at any specific level of repair divided by the total number of failures within an item repaired at that level during a particular interval under stated conditions.

### **Mean Time To Restore Functions (MTTRF)**

Mean time to restore functions is calculated as:

$$\text{MTTRF} = \frac{\text{total time down from critical failures}}{\text{number of critical failures}}$$

### **Measurement Accuracy**

The magnitude of the difference between the mean estimated value of a parameter and its true value (see definition). This estimate may be the result of a direct measurement, an indirect measurement, or an algorithmic derivation. The mean is based on a set of estimates satisfying the following two conditions:

- (1) The set is large enough so that the sample size error (see definition) in the measurement accuracy is much smaller than the specified measurement accuracy value.
- (2) The true value of the parameter is the same for all estimates in the set.

The second condition is imposed because a measurement accuracy requirement must be met for any true value of the parameter within the measurement range (see definition), not in an average sense over the measurement range. In practice, such as in the analysis of simulation results or measured calibration/validation data, it is understood that measurements will be binned into sets for which the true value of the parameters falls into a narrow range, preferably a range much smaller than the required measurement range.

For an ensemble of N estimates of the parameter x, the measurement accuracy  $\beta_N$  is given by the following formula:

$$\beta_N = |\mu_N - x_T|$$

where:  $\mu_N$  is the sample mean,  $x_T$  is the true value of the parameter, and  $|\dots|$  denotes absolute value. The sample mean  $\mu_N$  is given by the following formula:

$$\mu_N = (\sum_{i=1,N} x_i)/N$$

where:  $x_i$  is the value obtained in the i'th estimate of the parameter x and  $\sum_{i=1,N}$  denotes summation from i = 1 to i = N.

### **Measurement Error**

The difference between the estimated value of a parameter and its true value. This estimate may be the result of a direct measurement, an indirect measurement, or an algorithmic derivation.

The measurement error  $\epsilon$  is given by:

$$\epsilon = x_E - x_T$$

where:  $x_E$  is the estimate of the parameter x and  $x_T$  is its true value (see definition).

### **Measurement Precision**

The standard deviation (one sigma) of an estimated parameter. This estimate may be the result of a direct measurement, an indirect measurement, or an algorithmic derivation. The standard deviation is based on a set of estimates satisfying the following two conditions:

- (1) The set is large enough so that the sample size error (see definition) in the measurement precision is much smaller than the specified measurement precision value.
- (2) The true value of the parameter is the same for all estimates in the set.

The second condition is imposed because a measurement precision requirement must be met for any true value of the parameter within the measurement range (see definition), not in an average sense over the measurement range. In practice, such as in the analysis of simulation results or measured calibration/validation data, it is understood that measurements will be binned into sets for which the true value of the parameters falls into a narrow range, preferably a range much smaller than the required measurement range.

For an ensemble of N estimates of the parameter x, the measurement precision  $\sigma_N$  is given by the following formula:

$$\sigma_N = [ \sum_{i=1,N} (x_i - \mu_N)^2 / (N - 1) ]^{1/2}$$

where:  $\mu_N$  is the sample mean (defined in the definition of measurement accuracy),  $x_i$  is the value obtained in the i'th estimate of the parameter x, and  $\sum_{i=1,N}$  denotes summation from i = 1 to i = N.

### **Measurement Range**

Range of values over which a parameter is to be estimated while meeting all other measurement requirements. This estimate may be the result of a direct measurement, an indirect measurement, or an algorithmic derivation.

## Measurement Uncertainty

The root-mean-square (RMS) of the measurement errors (see definition) for an estimated parameter. This estimate may be the result of a direct measurement, an indirect measurement, or an algorithmic derivation. The measurement uncertainty is based on a set of estimates satisfying the following two conditions:

- (1) The set is large enough so that the sample size error (see definition) in the measurement uncertainty is much smaller than the specified measurement uncertainty value.
- (2) The true value of the parameter is the same for all estimates in the set.

The second condition is imposed because a measurement uncertainty requirement must be met for any true value of the parameter within the measurement range (see definition), not in an average sense over the measurement range. In practice, such as in the analysis of simulation results or measured calibration/validation data, it is understood that measurements will be binned into sets for which the true value of the parameters falls into a narrow range, preferably a range much smaller than the required measurement range.

As defined herein, measurement uncertainty is due to the combined effects of all systematic and random errors. Also, as a consequence of its definition, measurement uncertainty converges to the square root of the sum of the squares (RSS) of the measurement accuracy and precision in the limit of infinitely large sets of measurements.

For an ensemble of  $N$  estimates of a parameter  $x$ , the measurement uncertainty  $\xi_N$  is given by the following formula:

$$\xi_N = [\sum_{i=1,N} (x_i - x_T)^2 / N]^{1/2}$$

where:  $x_i$  is the value obtained in the  $i$ 'th estimate of the parameter,  $x_T$  is the true value of the parameter, and  $\sum_{i=1,N}$  denotes summation from  $i = 1$  to  $i = N$ .

## Mesh

A rectilinear (square) grid of lines which is superimposed upon a standard map projection. Current practice is to use a polar stereographic map projection for which each hemisphere is overlaid with a 512 x 512 square grid (called "eighth-mesh"), which is true at 60 degrees latitude, i.e., the quoted geographical grid size of the mesh (25 nmi) is true at 60 degrees latitude. A future upgrade would be the implementation of a sixteenth-mesh ("20 km") grid. ("Mesh" defined fields are also displayable as Mercator projection products.)

## Meteorological Range (Rm)

An empirically consistent measure of the visual range of a target. It is defined as the distance at which optical intensity is diminished by 17 dB (or the transmittance is 0.02). Meteorological Range  $\hat{E}(\mathbf{Rm}) = \hat{E}3.912/a_0$ , where  $a_0$  is the extinction coefficient. The extinction coefficient is defined by:

$$I(x) = I(0) e^{-x/a_0}$$

where:  $I(x)$  is the optical intensity at distance  $x$ .

## Mid-latitudes

The set of all locations on the earth's surface between 20 and 50 degrees north latitude and between 20 and 50 degrees south latitude.

## Mission Data

The combination of data provided by any of the mission sensors (i.e., environmental data) plus satellite orbit, attitude, and time tags. It does not include other sensors (i.e., S&R, SDC) or telemetry.

### **Mission Sensors**

Any sensor on the spacecraft directly used to satisfy any of the EDR requirements of TRD Appendix D.

### **Mixing Ratio**

In a sample of moist air, the mixing ratio is the ratio of the mass of water vapor to the mass of dry air. It is expressed in parts per thousand, usually grams of water vapor per kilogram of dry air.

### **Modulation Transfer Function (MTF)**

The magnitude of the Fourier transform of the end-to-end system point spread function (PSF). The MTF is a function of two spatial frequencies associated with two orthogonal spatial directions, and is equal to one at the origin by virtue of the normalization condition on the PSF.

### **Nephanalysis**

Analysis of cloud cover in terms of type and amount.

### **Objective**

A requirement which is significantly more difficult to meet than the threshold requirement but which, if met, would greatly enhance the utility of the data to the users.

### **On-Orbit Design Life**

The seven year period during which the satellite must meet all operational requirements.

### **Operational Availability**

Operational Availability ( $A_o$ ) is defined as the probability that a system is operable and ready to perform its mission at any given time.  $A_o$  is a function of mean time between critical failure (MTBCF) and mean time to restore functions (MTTRF) and shall be calculated as:

$$A_o = \frac{MTBCF}{MTBCF + MTTRF}$$

### **Operational Service Life**

The period of time that the NPOESS system has to be fully operational after IOC.

### **Operations Security (OPSEC)**

Actions taken or plans developed to protect information, classified or unclassified, which could reveal system plans, procedures, or missions.

### **Particle Size Parameter**

The Angstrom wavelength exponent, alpha, defined as:

$$a = - \Delta \ln (\tau) / \Delta \ln (\lambda)$$

where:  $\tau$  is optical thickness,  $\lambda$  is wavelength,  $\ln$  denotes natural logarithm, and  $\Delta$  denotes the difference between optical thickness measurements at two different wavelengths.

### **Payload**

Used to refer to the combination of the mission sensors and the SDC and S&R sensors carried by the spacecraft. The term may also be used to refer to the satellite when it is still mated to the launch vehicle.

### **Point Spread Function (PSF)**

See System Point Spread Function.

### **Precipitable Water Content**

The total amount of water and ice contained in a vertical column of the atmosphere.

### **Primary EDR**

EDR for which a sensor contractor has been assigned primary sensor and algorithm development responsibility, either under all conditions or prescribed conditions (e.g., clear versus cloudy conditions). The algorithm may or may not require the use of additional data from other sensors for which the EDR is not primary.

### **Probability of Correct Typing**

Probability that a horizontal cell reported as being of type  $x$  is in fact of type  $x$ , where  $x$  is any allowed type.

### **Radiance Reference Levels**

In the reference 0.4 - 1.0  $\mu\text{m}$  bandpass, an overhead sun at nadir produces a radiance of  $2.65 \times 10^{-2}$   $\text{W}/\text{cm}^2\text{-sr}$  at the location of the satellite for an earth surface albedo of unity; the radiance is  $5.7 \times 10^{-4}$   $\text{W}/\text{cm}^2\text{-sr}$  when the terminator is at nadir.

### **Raw Data Records (RDRs)**

Full resolution, unprocessed digital sensor data, time-referenced and earthlocated (or orbit-located for in-situ measurements), with radiometric and geometric calibration coefficients appended, but not applied, to the data. Aggregates (sums or weighted averages) of detector samples are considered to be full resolution data if the aggregation is normally performed to meet resolution and other requirements. Sensor data should be unprocessed with the following exceptions: time delay and integration (TDI), detector array non-uniformity correction (i.e., offset and responsivity equalization), and lossless data compression are allowed. All calibration data will be retained and communicated to the ground without lossy compression. Note that for the real time transmission of raw data to field terminals, lossy compression is allowed. Additionally, reduced resolution is allowed in transmission of raw data to low data rate field terminals.

### **Regional Resolution**

The smallest scale horizontal spatial resolution or horizontal cell size, defined in the TRD Appendix D, required by Centrals over specified regions. These regions might not be contiguous. Note that data at "regional resolution" is also transmitted to high data rate field terminals.

### **Reporting Frequency**

The mean time between successive reports of an EDR. Where reporting frequency is specified “per orbit” or “per satellite,” it is the mean time between successive reports of an EDR based on measurements from a single satellite. (Reporting frequency applies to EDR parameters that are not associated with localized portions of the earth's surface or a column of the atmosphere, e.g., in-situ measurements, solar irradiance measurements, etc. The times between consecutive observations of a parameter associated with a localized portion of the earth's surface or a column of the atmosphere are described by a constellation dependent distribution which varies from place to place. The attributes “maximum local average revisit time” and “maximum local refresh,” which are defined in terms of these earth location dependent distributions, are used for these EDR parameters.)

### **Sample Size Error**

The standard deviation of a function of a finite set of estimates of a parameter. These estimates may be the result of direct measurement, indirect measurement, or algorithmic derivation. The standard deviation is based on the ensemble of all possible finite sets of estimates. Sample size error is a measure of the width of the probability distribution of a function of a finite set of estimates.

If  $\theta_N(x_1, x_2, \dots, x_N)$  is a parameter depending on N estimates of a parameter x, i.e.,  $x_1, x_2, \dots, x_N$ , the sample size error is given by the following formula:

$$S_N = \langle (\theta_N(x_1, x_2, \dots, x_N) - \langle \theta_N(x_1, x_2, \dots, x_N) \rangle)^2 \rangle^{1/2}$$

where:  $\langle \dots \rangle$  denotes the expectation value over the ensemble of all possible sets of N estimates of x.

The measurement accuracy, precision, uncertainty, and short-term mean (see definition of long term stability) are all examples of functions of a finite set of estimates of a parameter.

### **Satellite**

The spacecraft and its sensor payload.

### **Sea Ice Properties**

Ice properties of the polar regions, including concentration, thickness, age, lead concentration, polynya concentration, iceberg distribution, etc.

### **Sea Surface Topography**

The height of the sea surface relative to the center of mass of the earth.

### **Secondary EDR**

EDR for which a sensor may provide data as a secondary input to an EDR algorithm assigned as a primary EDR to another sensor contractor, either under all conditions or prescribed conditions (e.g., clear versus cloudy conditions).

### **Secondary Mission Capability**

The secondary mission capability is provided when mission sensors other than the Imager and Profiler Suites are capable of delivering their RDRs to the C3S and IDPS, as required.

### **Sensor**

The mission-peculiar equipment or instrument to be manifested on a given space mission.

**Sensor Data Records (SDRs)**

Full resolution sensor data that are time referenced, earthlocated (or orbit-located for in-situ measurements), and calibrated by applying the ancillary information including radiometric and geometric calibration coefficients and georeferencing parameters such as platform ephemeris. These data are processed to sensor units (e.g., radar backscatter cross section, brightness temperature, radiance, etc.). Calibration, ephemeris, and any other ancillary data necessary to convert the sensor units back to sensor raw data (counts) are included.

**Sensor Suite**

One or more sensors needed to satisfy the EDR requirements allocated to a given Sensor Requirements Document (SRD). It does not include sensors from other SRD suites which provide secondary data contributions to those EDRs.

**Short-term Stability (TBR)****Short-wave Radiation**

The solar radiation that is reflected back by the Earth and the atmosphere. It is generally in the spectral wavelength interval between 0.3 and 4 micrometers.

**Significant Wave Height**

The average height of the largest one-third of the actual waves observed.

**Soil Moisture**

Moisture in the soil within the zone of aeration in cm/m (cm of water per meter of soil depth), including water vapor present in soil pores.

**Spacecraft**

The components and subsystems which support the sensor(s) and provide housekeeping functions such as orbit and attitude maintenance, navigation, power, command, telemetry and data handling, structure, rigidity, alignment, heater power, temperature measurements, etc.

**Space Segment**

The satellites (i.e., the spacecraft and their sensors) and their support equipment.

**Spectral Index**

Slope of the irregularity power spectrum of the electron energy density between two inverse scale lengths.

**System Point Spread Function (PSF)**

The end-to-end system response due to a point source at infinity in a given bandpass. In this SRD the PSF is considered to be a function of distance along the ground in two orthogonal directions. (A point source on the ground is considered to be "at infinity.") The PSF is normalized so that the two dimensional integral over the two orthogonal distance variables is equal to one. For a linear system, the system PSF can be expressed as a multiple convolution of the PSFs associated with all system components that contribute to the conversion of input radiance to the system output, e.g., the optics, detectors, signal and data processing.



## **Telemetry**

Health and status data of the satellite, including command authentication.

## **Temperature Data Records (TDRs)**

Geolocated antenna temperatures derived from microwave sensor data, together with all calibration, ephemeris, and other ancillary data necessary to convert the antenna temperatures back to sensor raw data (counts).

## **TEMPEST**

Short name referring to the investigation, study, and control of compromising emanations from telecommunications and automated information systems equipment.

## **Threshold**

The less stringent of the two requirements imposed on each measured or derived parameter. The more stringent requirement is the “objective.” (See definition above.) Failure to meet a threshold requirement for a non-key parameter renders the utility of the System questionable, at least to some segment of the user community. Failure to meet a threshold requirement for a key parameter is much more serious and places the entire program at risk. (See definition of “key parameter” above.)

## **Tides**

The periodic component of the sea surface topography induced by the gravitational interaction among the earth, moon, and sun.

## **Timeliness**

Elapsed time between the initiation of the measurement(s) necessary to generate an estimate of an environmental data characteristic and delivery of the EDR containing the estimate to the user site.

## **Total Water Content**

Total water content has two components:

- 1) Total columnar cloud liquid water content (CLWC), and
- 2) Total columnar integrated water vapor (TIWV).

## **True Value**

True value is defined in terms of (*TBR*) ground truth generally accepted in the user community. When the output of the sensor is folded into atmospheric, radiative transfer, and other models to produce EDRs, the measurement uncertainty of the EDR need not be traceable to an absolute reference standard, e.g., those maintained by the National Institute of Standards and Technology. The proof of meeting the measurement accuracy, precision, uncertainty, and long-term stability requirements has to be accomplished by analysis, laboratory measurements, simulations, and comparisons to ground based observations. The proof should include both sensor characteristics and the processing algorithms.

## **Unique Support Equipment (USE)**

Support equipment especially designed for use with a specific system and usable only on that system.

## **Users**

The people, such as weather forecasters, who employ the obtained environmental data.

## **Vegetation Index**

The identification of the predominant vegetation and/or soil type in a given area (see TRD Appendix D for details).

## **Vertical Cell Size**

For a parameter which is an estimate of the uniform spatial average of an environmental parameter within a square layer of the atmosphere, the vertical thickness of this layer. (For a parameter which is an estimate of an environmental parameter at a point, the vertical cell size is defined to be zero.)

## **Vertical Coverage**

The vertical spatial extent of the region within which estimates of an environmental parameter are made and reported.

## **Vertical Reporting Interval**

The spacing between nearest neighbor points along a local vertical at which an environmental parameter is estimated and reported. (This term is referred to as vertical sampling interval in the IORD; the terminology has been changed to avoid misinterpretation as an sensor measurement sampling interval.)

## **Visible Radiation**

The radiation that the human eye senses as part of the process of “seeing.” It is generally in the spectral wavelength interval between 0.4 and 0.7 micrometers. The blue end is near 0.4 micrometers and the red end is near 0.7 micrometers.

## **Wavelength Categories -- Visible/Infrared**

	Visible	0.4 - 0.7 $\mu\text{m}$
NIR	Near Infrared	0.7 - 1.5 $\mu\text{m}$
SWIR	Short-wave Infrared	1.5 - 3 $\mu\text{m}$
MWIR	Medium Wave Infrared	3 - 5 $\mu\text{m}$
LWIR	Long Wave Infrared	5 - 50 $\mu\text{m}$

**APPENDIX B**  
**SURVIVABILITY REQUIREMENTS**

## **APPENDIX B. SURVIVABILITY REQUIREMENTS**

Appendix B contains NPOESS survivability requirements and is classified. If applicable, Appendix B will be made available after contract award.

**APPENDIX C**  
**SENSOR DATA RECORD (SDR) CHARACTERISTICS (TBR)**

**APPENDIX D**

**NPOESS SYSTEM EDR REQUIREMENTS**

**DELETED—SEE TRD APPENDIX D ON CONTRACTOR LIBRARY**

**APPENDIX E**  
**NPOESS EDR/RDR MATRIX**

## APPENDIX E NPOESS EDR/RDR MATRIX

The real-time high data rate link will contain the following mission data (*TBR*):

- a) High (regional) resolution visual and IR imagery (with content similar to the current DMSP fine mode and NOAA High Resolution Picture Transmission).
- b) Other NPOESS sensor and associated sensor data needed by the HRD field terminals to meet the EDR processing requirements specified in Table E1.
- c) Other (TBS) data.

The real-time low data rate link will contain the following mission data (*TBR*):

- a) A (TBS) subset of real-time visual, visual night, and IR imagery (with content similar to the current NOAA Automatic Picture transmission or future Low Resolution Picture Transmission or DMSP's real time data smooth mode).
- b) Other NPOESS sensor and associated sensor data needed by the LDR field terminals to meet the EDR processing requirements specified in Table E1.
- c) Other (TBS) data.

The processing requirements for the Centrals, HDR, and LDR processing sites are shown in 50.1 NPOESS EDR/RDR Matrix.

**50.1 NPOESS EDR/RDR Matrix. R = RDRs and E = EDRs**

PARAMETER	DoD (NAVY)			DOC			DoD (AF/ARMY)		
	FNMOCC	HDR Field	LDR Field	NESDIS	HDR Field	LDR Field	AFGWC	50 WS	HDR Field
<b><u>ENVIRONMENTAL PARAMETERS</u></b>									
Vertical Moisture Profile	R/E	R/E		R	R	R	R/E		R/E
Vertical Temperature Profile	R/E	R/E		R	R	R	R/E		R/E
Temperature	R/E	R/E	R/E	R	R	R	R/E		R/E
Winds	R/E	R/E	R/E	R	R	R	R/E		R/E
	R/E	R/E		R	R	R	R/E		R/E
<b><u>OSPHERIC PARAMETERS</u></b>									
Cloud Thickness	R/E	R/E	R/E	R			R/E		R/E
Cloud Size	R/E	R/E	R/E	R			R/E		R/E
Column/Profile				R					
Water	R/E	R/E		R	R	R	R/E		R/E
Type/Rate	R/E	R/E	R/E	R	R	R	R/E		R/E
Phase/profile)	R/E	R/E	R/E	R			R/E		R/E
Attenuation	R/E	R/E	R/E	R			R/E		R/E
Content	R/E	R/E		R			R/E		
<b><u>LOUD PARAMETERS</u></b>									
Height	R/E	R/E	R/E	R	R	R	R/E		R/E
Layers	R/E	R/E	R/E	R	R	R	R/E		R/E
Particle Size	R/E	R/E		R	R	R	R/E		R/E
Scatter Path				R	R	R	R/E		R/E
Water	R/E	R/E		R	R	R	R/E		R/E
Depth/Transmittance	R/E	R/E		R	R	R	R/E		R/E
Height	R/E	R/E	R/E	R	R	R	R/E		R/E
Pressure				R	R	R	R/E		R/E
Temperature	R/E	R/E	R/E	R	R	R	R/E		R/E
<b><u>DIATION BUDGET PARAMETERS</u></b>									
Albedo	R/E	R/E	R/E	R			R/E		
Longwave Radiation (Surface)	R/E	R/E		R					
	R/E	R/E		R					
Shortwave Radiation (TOA)	R/E			R					
Longwave Radiation (TOA)	R/E			R					
	R/E			R					
<b><u>LAND PARAMETERS</u></b>									
Temperature	R/E	R/E		R	R	R	R/E		R/E
Differential Vegetation Index (NDVI)				R	R	R			
Depth	R/E	R/E	R/E	R	R	R	R/E		R/E
Surface Type	R/E	R/E	R/E	R	R	R	R/E		R/E

PARAMETER	DoD (NAVY)			DOC			DoD (AF/ARMY)		
	FNMOG	HDR Field	LDR Field	NESDIS	HDR Field	LDR Field	AFGWC	50 WS	HDRD Field
<b><u>ENVIRONMENTAL/WATER PARAMETERS</u></b>									
Wave	R/E	R/E	R/E	R					
Wave Motion	R/E	R/E		R	R	R	R/E		R/E
Temperature	R/E	R/E		R	R	R			
Current Transport	R/E	R/E		R			R/E		
Chlorophyll	R/E	R/E		R					
Characteristics	R/E	R/E		R	R	R			
Wind Sea Ice Motion	R/E	R/E	R/E	R	R	R	R/E		
Height/Topography	R/E	R/E	R/E	R	R	R			
Stress	R/E	R/E	R/E	R	R	R			
<b><u>ENVIRONMENTAL PARAMETERS</u></b>									
Aerosol				R				R/E	
Ice Deposition (Total)				R				R/E	
Ice Density				R				R/E	
Ionospheric Profile/Ionospheric specification				R				R/E	
Field	R/E	R/E	R/E	R				R/E	
Wave Velocity				R				R/E	
Ice Density				R				R/E	
Ice Fluctuations				R				R/E	
Ice Temperature				R				R/E	
Ice Crystallization				R				R/E	
Ice Profiles/Neutral Atmospheric				R				R/E	
High and Low Energy Solar Particles	R/E			R				R/E	
Galactic Cosmic Ray Particles	R/E			R				R/E	
Electron Flux				R				R/E	
Electron Flux through Auroral Energy Particles				R				R/E	
Auroral Airglow				R				R/E	
<b><u>OTHER PARAMETERS</u></b>									
Ice Collection				stored	real-time				
Ice Rescue					(TBR)				
Ice Available at the 13 S&R Mission									
Ice Sites and 25 S&R Local User									
Ice Sites									

**APPENDIX F**  
**ACRONYMS AND ABBREVIATIONS**

## APPENDIX F ACRONYMS and ABBREVIATIONS

%CVCM.....	Percent Collected Volatile Condensable Material	CVCM .....	Collected Volatile Condensable Material
%TML.....	Percent Total Mass Loss	dB .....	Decibels
$\Delta$ Trms.....	Root Mean Square Temperature Difference	DEW .....	Directed Energy Weapon
AFOSI.....	Air Force Office of Special Investigations	DMSP .....	Defense Meteorological Satellite Program
AMSU-A .....	Advanced Microwave Sounding Unit-A	DOC.....	Department of Commerce
Ao.....	Operational Availability	DOD .....	Department of Defense
ASAT .....	Anti-satellite	ECCM.....	Electronic Counter-Counter Measures
ASD.....	Acceleration Spectral Density	EDR .....	Environmental Data Record
ASTM.....	American Society for Testing and Materials	EED .....	Electro-Explosive Device
BC .....	Bus controller	EELV .....	Evolved Expendable Launch Vehicle
BIT .....	Built-In-Test	EESS.....	Earth Environmental Sensor System
Btu/hr-ft <sup>2</sup> .....	British Thermal Units per hour-foot squared	EMC .....	Electromagnetic Compatibility
C.....	Centigrade	EMI.....	Electromagnetic Interference
CCSDS .....	Consultative Committee for Space Data Systems	EO.....	Electro-optical
C&DH .....	Command and Data Handling	EPCRA .....	Emergency Planning and Community Right to Know Act
C&T .....	Command and Telemetry	ESD .....	Electro-Static Discharge
C3.....	Command, Control, and Communications	EW.....	Electronic Warfare
C3S.....	Command, Control, and Communications Segment	FFT .....	Fast Fourier Transform
CCA .....	Contamination Control Analysis	FOR .....	Field of Regard
CCP.....	Contamination Control Plan	FOV .....	Field of View
c.g.....	Center of Gravity	Fsu .....	Factor of Safety - ultimate
CI .....	Configuration Item	Fsy .....	Factor of Safety - yield
CMIS.....	Conical Scanning Microwave Imager/Sounder	g.....	Gram
CNR .....	Carrier-to-Noise Ratio	GFE .....	Government Furnished Equipment
COMPUSEC.....	Computer Security	GHz.....	Giga-Hertz
COMSEC .....	Communications Security	GLONASS .....	Russia's Global Navigation Satellite System
COTS .....	Commercial Off-The-Shelf	GMM .....	Geometric Math Model
CrIMSS .....	Cross-track Infrared/Microwave Sounding Suite	GPS.....	Global Positioning System
CrIS .....	Cross-track Infrared Sounder	GPSOS .....	Global Positioning System Occultation Sensor
CSCI.....	Computer Software Configuration Item	GSD .....	Ground Sample Distance
		GSE .....	Ground Support Equipment
		HPBW .....	Half-Power Beam Width
		HSR .....	Horizontal Spatial Resolution

HWCI.....	Hardware Configuration Item	NEDN .....	Noise Equivalent Difference Irradiance
Hz.....	Hertz	NEDT .....	Noise Equivalent Temperature Difference
I&T.....	Integration and Test	NESDIS .....	National Environmental Satellite, Data, and Information Service
ICD.....	Interface Control Document	NIST .....	National Institute of Standards and Technology
IDPS.....	Interface Data Processor Segment	NOAA.....	National Oceanic and Atmospheric Administration
IFOR.....	Instantaneous Field of Regard	NOFORN .....	Not Releasable to Foreign Nationals
Ifov .....	Instantaneous Field of View	NPOESS.....	National Polar-Orbiting Operational Environmental Satellite System
IGS .....	Inertial Guidance System	NTIA.....	National Telecommunications and Information Agency
ILS .....	Integrated Logistics Support	NRZ .....	Not Return To Zero
IOC.....	Initial Operational Capability	ns .....	Nano-seconds
IOD.....	Integrated Operational Requirements Document	NVR.....	Non-Volatile Residue
IOT&E .....	Initial Operational Test and Evaluation	OATS.....	Government Operational Algorithm Teams
IPO .....	Integrated Program Office	ODS .....	Ozone Depleting Substance
IR .....	Infrared	OMPS .....	Ozone Mapping and Profiler Suite
IRD.....	Interface Requirements Document	OPD .....	Optical Path Difference
ITU.....	International Telecommunications Union	ORD.....	Operational Requirements Document
IW .....	Information Warfare	P3I .....	Potential Pre-Planned Product Improvement
JSC.....	NASA Johnson Spaceflight Center	PDR .....	Preliminary Design Review
kbps .....	kilobits per second	PHS&T.....	Packaging, Handling, Storage, and Transportation
KEW .....	Kinetic Energy Weapon	PLF .....	Payload Fairing
Kg .....	Kilogram	POD .....	Precise Orbit Determination
kHz.....	Kilohertz	POES .....	Polar-orbiting Operational Environmental Satellite
LHCP.....	Left-hand Circular Polarization	pps .....	Pulses Per Second
LOS .....	Line-of-Sight	RDR.....	Raw Data Record
LST .....	Land Surface Temperature	RHCP.....	Right-hand Circular Polarization
LV .....	Launch Vehicle	RMS.....	Root Mean Square
m .....	Meters	RT.....	Remote Terminal
METOP .....	EUMETSAT Meteorological Observation Satellite System	S&R .....	Search and Rescue
MHS.....	Microwave Humidity Sounder	S/A.....	Selective Availability
MLI .....	Multi-Layer Insulation	SCA .....	Satellite Control Authority
MLV.....	Medium Launch Vehicle	SDC .....	Surface Data Collection
MMA .....	Moving Mechanical Assembly		
MTBCF .....	Mean Time Between Critical Failure		
MTTRF .....	Mean Time To Restore Function		
NAIC.....	National Air Intelligence Center		
NASA.....	National Aeronautics and Space Administration		
NEA .....	Non-Explosive Actuator		

SDR..... Sensor Data Record  
 SGLS..... Satellite Ground Link System  
 SI..... International System of Units  
 (Metric)  
 SINDA..... Systems Improved Numerical  
 Differencing Analyzer  
 SIP..... Standard Interface Plane  
 SNR..... Signal-to-Noise Ratio  
 SOC..... Satellite Operations Center  
 SOH..... State of Health  
 SRD..... Sensor Requirements Document  
 SRR..... System Requirements Review  
 SS..... Space Segment  
 SST..... Sea Surface Temperature  
 STAR ..... Systems Threat Assessment Report  
 SV ..... Space Vehicle  
 TAR..... Tape Archives  
 TBD..... To Be Determined (by contractor)  
 TBR..... To Be Resolved (by  
 contractor/government)  
 TBS ..... To Be Supplied (by government)  
 TDR..... Temperature Data Record  
 TEMPEST ..... Computer Emissions Security  
 Standard  
 TML ..... Total Mass Loss  
 TMM..... Thermal Math Model  
 TRASYS..... Thermal Radiation Analysis  
 System  
 TRD..... Technical Requirements Document  
 TSPR..... Total System Performance  
 Responsibility  
 Tu..... Third Stokes Parameter  
 Tv..... Fourth Stokes Parameter  
 ULOSA..... Unit-Level Open System  
 Architecture  
 USAF..... United States Air Force  
 USG..... United States Government  
 UTC..... Universal Time Code  
 UV..... Ultraviolet  
 V ..... Vertical  
 VIIRS ..... Visible/Infrared  
 Imager/Radiometer Suite  
 VSWR ..... Voltage Standing Wave Ratio

WNINTEL ..... Warning Notice - Intelligence  
 Sources

**APPENDIX G**  
**POTENTIAL PRE-PLANNED PRODUCT IMPROVEMENTS**

## APPENDIX G POTENTIAL PRE-PLANNED PRODUCT IMPROVEMENTS

70.1 Potential Pre-planned Product Improvements. This paragraph describes elements of the NPOESS mission needs having potentially restrictive technical or programmatic uncertainties identified as a result of Phase 0 Concept studies. DOC and DoD maintain a need for these observations, and prioritize them in terms of mission criticality below. The NPOESS Demonstration/Validation (Phase 1) allows for continued examination of possible solutions to these needs, including new or modified instrumentation in future space segments beyond NPOESS IOC. Candidate technologies for meeting these needs should be examined in NPOESS Phase 1 for possible inclusion at a later time. No thresholds are stated.

70.1.1 Tropospheric Winds (DOC/DoD). Wind measured throughout the troposphere. Wind profile required for cloud returns and planetary boundary layer aerosol returns.

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage	N/A	Surface to 20 km
b. Horizontal Cell Size	N/A	50 km
c. Vertical Sampling Interval	N/A	0.1 km
d. Mapping Uncertainty	N/A	10 km
e. Measurement Range	N/A	0-100 m/s
f. Measurement Precision	N/A	0.5 m/s, vector winds
g. Measurement Accuracy	N/A	1 m/s, horiz. components
h. Maximum Local Average Revisit Time	N/A	1 hour

70.1.2 Ozone Profile - High-Resolution (DOC). Measurement of ozone concentration within a specified volume.

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage	N/A	(TBD)
b. Horizontal Cell Size (Profile)	N/A	250 km
c. Vertical Cell Size (Profile)		
1. 0-10 km	N/A	3 km
2. 10-25 km	N/A	1 km
3. 25-60 km	N/A	3 km
d. Mapping Uncertainty (Profile)	N/A	25 km
e. Measurement Range (Profile)		
1. 0-10 km	N/A	0.01-3 ppmv
2. 10-60 km	N/A	0.1-15 ppmv
f. Measurement Precision (Profile)		
1. 0-10 km	N/A	10 %
2. 10-15 km	N/A	3 %
3. 15-50 km	N/A	1 %
4. 50-60 km	N/A	3 %
g. Measurement Accuracy (Profile)		
1. 0-10 km: N/A	N/A	10 %
2. 10-15 km: 20 %	N/A	10 %
3. 15-60 km: 10 %	N/A	5 %
h. Maximum Local Average Revisit Time (Profile)	N/A	24 hours
i. Long Term Stability (Profile)	N/A	1 %

70.1.3 CH<sub>4</sub> (Methane) Column (DOC). Measure of amount of methane contained in a specified volume of air.

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage	N/A	Total column
b. Horizontal Cell Size	N/A	100 km
c. Mapping Uncertainty	N/A	25 km
d. Measurement Range	N/A	40-80 moles/cm <sup>2</sup>
e. Measurement Precision	N/A	1 %
f. Measurement Accuracy	N/A	5 %
g. Maximum Local Average Revisit Time	N/A	24 hours

70.1.4 CO (Carbon Monoxide) Column (DOC). Measure of carbon monoxide in a specified volume of air.

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage	N/A	Total column
b. Horizontal Cell Size	N/A	100 km
c. Mapping Uncertainty	N/A	25 km
d. Measurement Range	N/A	0 - 7 moles/cm <sup>2</sup>
e. Measurement Precision	N/A	3 %
f. Measurement Accuracy	N/A	5 %
g. Maximum Local Average Revisit Time	N/A	24 hours

70.1.5 CO<sub>2</sub> (Carbon Dioxide) Column (DOC). Retrievals of column and total carbon dioxide, calibrated by the users with ground-based measurements, of stated precision needed to afford deduction of long-term variations and trends.

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage	N/A	Total column
b. Horizontal Cell Size	N/A	100 km
c. Mapping Uncertainty	N/A	25 km
d. Measurement Range	N/A	11,000 - 15,000 moles/cm <sup>2</sup>
e. Measurement Precision	N/A	15-20 moles/cm <sup>2</sup>
f. Measurement Accuracy	N/A	(TBD)
g. Maximum Local Average Revisit Time	N/A	24 hours

70.1.6 Optical Backgrounds (DoD). Emissions are the result of interactions between precipitating energetic particles and solar ultraviolet radiation with neutral atmospheric constituents.

	<u>Thresholds</u>	<u>Objectives</u>
a. Coverage	N/A	Global
b. Horizontal Cell Size	N/A	10 km
c. Mapping Uncertainty	N/A	50 km
d. Measurement Range		
1. Wavelength	N/A	1-29 microns, 0.4-0.7 microns, 0.04-0.2 microns
2. Brightness	N/A	(TBD)
e. Measurement Precision	N/A	(TBD)
f. Measurement Accuracy	N/A	(TBD)
g. Maximum Local Average Revisit Time	N/A	each orbit

70.1.7 Bathymetry (Deep Ocean and Near Shore) (DoD). Vertical depth of water.

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage		
1. Deep Ocean	N/A	0-300 m
2. Near shore	N/A	0-200 m
b. Horizontal Cell Size		
1. Deep Ocean	N/A	300 m
2. Near shore	N/A	(TBD)
c. Vertical Cell Size	N/A	1 m
d. Mapping Uncertainty	N/A	10 m
e. Measurement Range		
1. Deep Ocean	N/A	0-300 m
2. Near shore	N/A	0-200 m
f. Measurement Accuracy	N/A	0.3 m
g. Maximum Local Average Revisit Time	N/A	(TBD)

70.1.8 Bioluminescence (DoD). A measurement of the number of bioluminescent organisms present in sea water within a region.

	<u>Thresholds</u>	<u>Objectives</u>
a. Horizontal Cell Size	N/A	(TBD)
b. Mapping Uncertainty	N/A	(TBD)
c. Measurement Accuracy	N/A	(TBD)
d. Maximum Local Average Revisit Time	N/A	(TBD)

70.1.9 Salinity (DoD/DoC). A measure of the quantity of dissolved materials in sea water. A formal definition is “the total amount of solid materials, in grams, contained in one kilogram of sea water, when all the carbonate has been converted to oxide, the bromine and iodine converted to chlorine, and all organic matter is completely oxidized. Units of measurement are parts per thousand, by weight.”

	<u>Thresholds</u>	<u>Objectives</u>
a. Vertical Coverage	N/A	0-300 m
b. Horizontal Cell Size		
1. Global	N/A	20 km
2. Regional	N/A	0.25 km
c. Vertical Cell Size		
1. Global	N/A	10 m
2. Regional	N/A	2 m
d. Mapping Uncertainty		
1. Global	N/A	5 km
2. Regional	N/A	0.25 km
e. Measurement Range	N/A	0-40 ppt
f. Measurement Precision	N/A	0.1 ppt
g. Measurement Accuracy		
1. Global	N/A	<i>(TBD)</i>
2. Regional	N/A	0.5 ppt
h. Maximum Local Average Revisit Time	N/A	72 hours

**APPENDIX H**  
**TEST VERIFICATION MATRIX**  
**(TBD)**